

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 5960-5 (2001): Meat and Meat Products - Methods of Test, Part 5: Determination of Moisture Content (Reference Method) [FAD 18: Slaughter House and Meat Industry]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



भारतीय मानक

मांस और मांस उत्पाद — परीक्षण पद्धति
भाग 5 नमी की मात्रा का निर्धारण (संदर्भ विधि)
(पहला पुनरीक्षण)

Indian Standard

**MEAT AND MEAT PRODUCTS —
METHODS OF TEST**

PART 5 DETERMINATION OF MOISTURE CONTENT (REFERENCE METHOD)

(First Revision)

ICS 67.120.10

© BIS 2001

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

NATIONAL FOREWORD

This Indian Standard (Part 5) (First Revision) which is identical with ISO 1442 : 1997 'Meat and meat products — Determination of moisture content (Reference method)' issued by the International Organization for Standardization (ISO) was adopted by the Bureau of Indian Standards on the recommendation of the Slaughter House and Meat Industry Sectional Committee and approval of the Food and Agriculture Division Council.

This standard was originally published in 1971. It is being revised to harmonize with ISO 1442:1997 under dual numbering.

In the adopted standard certain terminology and conventions are not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appear, referring to this standard, they should be read as 'Indian Standard'; and
- b) Comma (,) has been used as a decimal marker while in Indian Standards the current practice is to use a point (.) as the decimal marker.

In this adopted standard, the following International Standards are referred to. Read in their respective places the following:

<i>International Standard</i>	<i>Corresponding Indian Standard</i>	<i>Degree of Equivalence</i>
ISO 3100-1 : 1991 Meat and meat products — Sampling and preparation of test samples — Part 1: Sampling	IS/ISO 3100-1:1991 Meat and meat products — Method of sampling	Identical
ISO 5725-1 : 1994 Accuracy (true-ness and precision) of measurement methods and results: Part 1 General principles and definitions	IS 7920 (Part 1) : 1994 Statistical vocabulary and symbols: Part 1 Probability and statistical terms (<i>second revision</i>)	Related

In reporting the results of a test or analysis made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'.

Indian Standard
**MEAT AND MEAT PRODUCTS —
METHODS OF TEST**
PART 5 DETERMINATION OF MOISTURE CONTENT (REFERENCE METHOD)
(First Revision)

1 Scope

This International Standard specifies a reference method for the determination of the moisture content of meat and meat products.

2 Definitions

For the purposes of this International Standard, the following definitions apply.

2.1 moisture content of meat and meat products: Loss in mass obtained under the operating conditions specified in this International Standard, divided by the mass of the test portion.

Moisture content is expressed as a percentage by mass.

2.2 test result: The value of a characteristic obtained by carrying out a specified test method. [ISO 5725-1]

3 Principle

Thorough mixing of the test portion with sand and drying to constant mass at 103 °C ± 2 °C.

4 Material

4.1 Sand, clean, acid-washed, of a size such that it passes through a sieve of aperture size 1,4 mm and stays on a sieve of aperture size 250 μ m.

Dry the sand before use at 150 °C to 160 °C and store in an airtight closed bottle.

NOTE — If clean (acid-washed) sand is not available, the sand may be cleaned by the following procedure.

Wash the sand with running water. Boil the sand with dilute hydrochloric acid, $\rho_{20} = 1,19$ g/ml, diluted (1 + 1), for 30 min while stirring continuously. Repeat the boiling operation with another portion of the acid until the acid no longer turns yellow after boiling. Wash the sand with distilled water until the test for chloride is negative. For storage, dry the sand at 150 °C to 160 °C.

5 Apparatus

Usual laboratory apparatus and, in particular, the following.

5.1 Mechanical or electrical equipment capable of homogenizing the laboratory sample. This includes a high-speed rotational cutter, or a mincer fitted with a plate with holes not exceeding 4,0 mm in diameter.

5.2 Flat dish, made of porcelain or metal (e.g. nickel, aluminium, stainless steel), of diameter at least 60 mm and height about 25 mm.

5.3 Thin glass rod, flattened at one end, slightly longer than the diameter of the dish (5.2).

5.4 Drying oven, electrically heated, capable of operating at 103 °C ± 2 °C.

5.5 Desiccator, containing an efficient desiccant, such as silica gel.

5.6 Analytical balance, capable of weighing to the nearest 0,001 g.

6 Sampling

It is important that the laboratory receive a sample which is truly representative and has not been damaged or changed during transport or storage.

Sampling is not part of the method specified in this International Standard. A recommended sampling method is given in ISO 3100-1.

Proceed from a representative sample of at least 200 g.

Store the sample in such a way that deterioration and change in composition are prevented.

7 Preparation of test sample

Homogenize the laboratory sample with the appropriate equipment (5.1). Take care that the temperature of the sample material does not rise above 25 °C. If a mincer is used, pass the sample at least twice through the equipment. Fill a suitable airtight container with the prepared test sample, close the container and store in such a way that deterioration and change in composition are prevented. Analyse the test sample as soon as practicable, but always within 24 h after homogenization.

8 Procedure

NOTE — If it is required to check whether the repeatability limit (10.2) is met, carry out two single determinations in accordance with 8.3 under repeatability conditions.

8.1 Preparation of the dish and sand

Transfer to the dish (5.2) a quantity of sand (4.1) equal to three to four times the mass of the test portion (see 8.2) and dry the dish, sand and glass rod (5.3) for 30 min in the oven (5.4) set at 103 °C.

Allow the dish with its contents and the glass rod to cool in the desiccator (5.5) to room temperature and weigh to the nearest 0,001 g (m_0).

8.2 Test portion

Transfer between 5 g to 8 g of the prepared test sample (clause 7) to the prepared dish (8.1) and weigh the dish with its contents and the glass rod to the nearest 0,001 g (m_1).

8.3 Determination

8.3.1 Mix the contents of the dish by means of the glass rod (5.3).

NOTE — In cases of difficulty in mixing the test portion with sand, ethanol may be added as necessary. In this case, the ethanol should be evaporated gently before drying the sample in the oven.

Heat the dish with its contents and the glass rod for 2 h in the oven (5.4) set at 103 °C. Remove the dish with its contents and the glass rod from the oven and place them in the desiccator (5.5).

Allow the dish, its contents and the glass rod to cool to room temperature, then weigh to the nearest 0,001 g.

8.3.2 Repeat the heating, cooling and weighing operations specified in 8.3.1 until the results of two successive weighings (m_2), separated by 1 h of heating, do not differ by more than 0,1 % of the mass of the test portion.

9 Expression of results

Calculate the moisture content, w , as a percentage by mass, using the following equation:

$$w = \frac{m_1 - m_2}{m_1 - m_0} \times 100 \%$$

where

m_0 is the mass, in grams, of the dish, rod and sand (8.1);

m_1 is the mass, in grams, of the dish containing the test portion, rod and sand, before drying (8.2);

m_2 is the mass, in grams, of the dish containing the test portion, rod and sand, after drying (8.3.2).

Report the result rounded to one decimal place.

10 Precision

10.1 Interlaboratory test

Details of an interlaboratory test on the precision of the method are given in ref. [3]. The values derived from this interlaboratory test may not be applicable to concentration ranges and matrices other than those given.

10.2 Repeatability

The absolute difference between two independent single test results, obtained using the same method on identical test material in the same laboratory by the same operator using the same equipment within a short interval of time, should not be greater than the value of r given by the formula

$$r = 0,593 \% + 0,0017 \bar{w}$$

where \bar{w} is the mean moisture content of both results, expressed as a percentage by mass.

10.3 Reproducibility

The absolute difference between two single test results obtained using the same method on identical test material in different laboratories with different operators using different equipment, should not be greater than the value of R given by the formula.

$$R = 0,797 \% + 0,00471 \bar{w}$$

where \bar{w} is the mean moisture content of both results, expressed as a percentage by mass.

11 Test report

The test report shall specify

- the method in accordance with which sampling was carried out (if known);
- the method used;
- the test result(s) obtained; and
- if the repeatability has been checked, the final quoted result obtained.

It shall also mention all operating details not specified in this International Standard, or regarded as optional, together with details of any incidents which may have influenced the result.

The test report shall include all information necessary for the complete identification of the sample.

Annex A **(informative)**

Bibliography

- [1] ISO 3100-1:1991, *Meat and meat products — Sampling and preparation of test samples — Part 1: Sampling.*
- [2] ISO 5725-1:1994, *Accuracy (trueness and precision) of measurement methods and results — Part 1: General principles and definitions.*
- [3] Nordic Committee on Food Analysis (NMKL), No. 23, 3rd edn., 1991. Available from NMKL, Statens Tekniska Forskningscentral, Livmedelslaboratoriet, SF-02150 Esbo, Finland.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc : No. FAD 56 (483).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters :

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110 002
Telephones : 323 01 31, 323 33 75, 323 94 02

Telegrams : Manaksanstha
(Common to all offices)

Regional Offices :

	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110 002	{ 323 76 17 323 38 41
Eastern : 1/14 C.I.T. Scheme VII M, V. I. P. Road, Kankurgachi KOLKATA 700 054	{ 337 84 99, 337 85 61 337 86 26, 337 91 20
Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160 022	{ 60 38 43 60 20 25
Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600 113	{ 254 12 16, 254 14 42 254 25 19, 254 13 15
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) MUMBAI 400 093	{ 832 92 95, 832 78 58 832 78 91, 832 78 92
Branches : AHMEDABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. NAGPUR. NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM.	